

## Air heaters for agriculture and horticulture

Product brochure · GB

**Edition** 10.12



## Technical specifications

### Air heaters for natural gas or LPG

Type	Capacity	Air output	Jet length	Consumption	
				Natural gas (H)	Propane
ERA33 230 V	33 kW	1,700 m <sup>3</sup> /h	30 m	3.5 m <sup>3</sup> /h	2.4 kg/h
GP14 230 V	14 kW	1,200 m <sup>3</sup> /h	10 m	1.1 m <sup>3</sup> /h	1.0 kg/h
GP40 230 V	40 kW	3,900 m <sup>3</sup> /h	40 m	3.6 m <sup>3</sup> /h	3.1 kg/h
GP70 230 V	70 kW	4,500 m <sup>3</sup> /h	50 m	6.1 m <sup>3</sup> /h	5.0 kg/h
GP95 230 V	95 kW	6,500 m <sup>3</sup> /h	40 m	7.8 m <sup>3</sup> /h	6.8 kg/h
GP120 230 V	120 kW	8,000 m <sup>3</sup> /h	50 m	9.9 m <sup>3</sup> /h	8.6 kg/h

### Air heaters for diesel or kerosene

Type	Capacity	Air output	Jet length	Consumption
P40 230 V	40 kW	4,400 m <sup>3</sup> /h	30 m	4 l/h
P60 230 V	60 kW	6,200 m <sup>3</sup> /h	30 m	6 l/h
P80 230/400 V	80 kW	7,700 m <sup>3</sup> /h	40 m	8 l/h
P100 230/400 V	100 kW	7,700 m <sup>3</sup> /h	40 m	10 l/h
P120 230/400 V	120 kW	7,700 m <sup>3</sup> /h	50 m	12 l/h

### Air heaters with chimney for diesel or kerosene

Type	Capacity	Air output	Jet length	Consumption
RGA95 garden 230/400 V	95 kW	8,000 m <sup>3</sup> /h	40 m	10 l/h
RGA95 stable 230 V	95 kW	8,000 m <sup>3</sup> /h	40 m	10 l/h

### Air heaters with chimney for natural gas or LPG

Type	Capacity	Air output	Throw	Consumption	
				Natural gas (H)	Propane
RGA100 230 V	100 kW	8,000 m <sup>3</sup> /h	40 m	8.0 m <sup>3</sup> /h	6.9 kg/h

### Circulation fans

Type	Air output	Jet length
R20-9	5,800 m <sup>3</sup> /h	45 m
R20-14	8,600 m <sup>3</sup> /h	60 m

ermaf is the global market leader in the field of agricultural air heaters.

The high quality components and robust stainless steel design make ermaf air heaters ideally suited for use in intensive livestock breeding and horticulture.

ermaf has more than 30 years' practical experience in the field of air heaters.

The product range includes gas- and oil-fired air heaters for mobile and stationary use with heating capacities of between 14 and 120 kW.

Continuous development as regards optimizing combustion and efficiency ensure eco-

nomical and reliable operation. The devices are characterized by their long service life and ultra-clean combustion as well as being easy to use and easily accessible for cleaning and servicing.

The safety components in ermaf air heaters comply with the highest standards due to their Class A valves and ionization flame control.

ermaf devices do, of course, comply with European standards as well as with the requirements of countries outside Europe.



ERA 33




GP 70



GP 95



P



P mobil



RGA 95



RGA 100



Recirculation fan

## Contact

[www.ermaf.nl](http://www.ermaf.nl) → Sales contacts

Elster GmbH  
Postfach 2809 · 49018 Osnabrück  
Strothweg 1 · 49504 Lotte (Büren)  
Germany

T +49 541 1214-0  
F +49 541 1214-370  
[orders.ermaf@elster.com](mailto:orders.ermaf@elster.com)  
[www.ermaf.nl](http://www.ermaf.nl)